

Please ensure that this SDS is received by the appropriate persons

Review Date: 18/07/2022 v01 Emergency: 0860 02 02 02 Document Number: AFX-SDS-0021

1. PRODUCT AN	ID COMPANY IDENTIFICATION
Product	Argon
Synonym	Argon
Chemical Formula	Ar
Trade Name	Technical Argon
	HP Argon
	Baseline Argon
Colour Coding	Peacock blue
Product Code	10-SE
	11-SE / 11-ME15
	512203-SE-C
Company	African Oxygen Limited
Identification	Grayston Office Park Building 7
	128 Peter Road Sandown, Sandton,
	2196
	Tel. No: (011) 490-0400
	Fax No: (011) 490-0530
	Email:
	customer.service@afrox.linde.com
	www.afrox.com
Emergency	
Numbers	0860 02 02 02 (Afrox)

GHS Precautionary Statements	Storage: - P403 : Store in a well-ventilated place. Prevention: - P280 : Wear protective gloves/eye protection/face protection. Response: - None Disposal - None
Other Hazards that do not result in classification	- Asphyxiant in high concentrations

3. COMPOSITION OF INGREDIENTS		
Chemical name	Argon	
Chemical family	Argon	
CAS No	7440-37-1	
UN No	1006 (gas)	
	1755 (liquid)	
ERG No	121 (gas)	
	123 (liquid)	
Hazard class	Class 2.1	
Hazchem Warning	Compressed gas	

2. HAZARD IDENTIFICATION		
Classification	- Classification under South African Hazardous Chemical Substances Regulations subsequently amended. (HCS)	
	-Classification under the Globally Harmonized System of classification and labelling of chemicals (GHS)	
Emergency Overview	Colour: None Odour: None Taste: None Physical State: Compressed Gas Form: Gas under pressure	
	- All cylinders are portable gas containers and must be regarded as pressure vessels at all times Argon does not support life.	
Adverse Health Effects	- Asphixiant	
Chemical Hazards	- Asphyxiant.	
Biological Hazards	- The greatest physiological effect of Argon is to cause asphyxiation.	
Vapour Inhalation	- Asphyxiation	
GHS Classification	- Gas under pressure	
GHS Pictogram	\Diamond	
GHS Signal Words	Warning	
GHS Hazard Statements	- H280: Contains gas under pressure, may explode if heated	



Please ensure that this SDS is received by the appropriate persons

Review Date: 18/07/2022 v01 Emergency: 0860 02 02 02 Document Number: AFX-SDS-0021

5. FIRE-FIGHTING MEASURES	
Suitable extinguishing media	Material will not burn. In case of fire in the surroundings: use appropriate extinguishing agent
Unsuitable extinguishing media:	- None
Specific Hazards	- Asphyxiant - Liquid may cause cryogenic burns.
Special fire fighting procedures:	- In case of fire: Stop leak if safe to do so. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire.
Special protective equipment for firefighters:	- Exposed Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces a self-contained breathing apparatus

- ACCIDENTAL DELEACE MEACURES		
6. ACCIDENTAL RELEASE MEASURES		
Personal precautions, protective equipment and emergency procedures:	- WARNING! Liquid and gas under pressure. Rapid release of gaseous Argon through a pressure relief device (PRD) or valve can result is very cold and can cause frostbite.	
	 Evacuate area. Provide adequate ventilation. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. 	
	- In an enclosed or non-ventilated space, a self-contained breathing apparatus must be used	
Environmental Precautions	- Prevent further leakage or spillage if safe to do so	
Methods and material for containment and cleaning up:	- Provide adequate ventilation	

7. HANDLING	AND STORAGE
Safe Handling	-Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide

	adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps were supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.
Conditions for safe storage, including any incompatibilities	-Containers should not be stored in conditions likely to encourage corrosion. Keep away from food, drink and animal feeding stuffs. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION	
Occupational Exposure Hazards (HCS)	-Not specified
Engineering Control Measures	- Engineering control measures are preferred to reduce exposures. General methods include mechanical ventilation, process or personal enclosure, and control of process conditions. Administrative controls and personal protective equipment may also be required. A Risk assessment should be conducted to evaluate the suitability of
	PPE to the task being performed
Personal Protection	- When allowed by a risk assessment Respiratory Protective Equipment (RPE)

combustible material.

from sources of heat and ignition. Keep pressure containers away from



Please ensure that this SDS is received by the appropriate persons

Review Date: 18/07/2022 v01 Emergency: 0860 02 02 02 Document Number: AFX-SDS-0021

Eyes	may be used. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD. Self-contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres Wear safety glasses
Lyco	vvoar saroty glasses
Hands	-Guideline: Protective gloves against mechanical risks Additional Information: Wear working gloves while handling containers
Body protection:	-Wear leather apron when handling liquid containers
Feet	- Wear safety shoes while handling containers

9. PHYSICAL AND CHEMICAL PROPERTIES	
Chemical Name	Argon
Chemical Symbol	Ar
Physical state	Gas
Form:	Gas
Colour:	Colourless
Odour:	Odourless
Odour Threshold:	No odour
pH:	No effect in water
Melting Point:	NA
Boiling Point:	−185.87 °C
Sublimation Point:	NA
Critical Temp. (°C):	-122.29 °C
Flash Point:	Not applicable
Evaporation Rate:	Not applicable.
Flammability (gas):	Non Flammable
Flammability limit - upper (%):	NA
Flammability limit - lower(%):	NA
Vapour pressure:	Permanent gas
Vapour density (air=1)	1.66 @ 20°C
Relative density:	1.36 @ 20 °C)
Solubility(ies)	
Solubility in Water:	0.033 l/kg water 20°C
Partition coefficient (n-octanol/water):	Not known
Autoignition Temperature:	Not applicable.
Decomposition Temperature:	Not known.
Viscosity	
Kinematic viscosity:	No data available.
Dynamic viscosity:	Not applicable
Explosive properties:	Not applicable
Oxidising Properties:	Not applicable
Molecular weight	39.95 g/mol

10. STABILITY AND REACTIVITY	
Reactivity	-Not reactive
Chemical stability	- Stable under normal conditions.

Possibility of hazardous reactions	- Gas under high pressure. Accumulate in low lying areas.
Conditions to avoid	 Overheating of cylinders. Never use cylinders as rollers or supports; or for any other purpose than the storage of Argon
Incompatible Materials	None
Hazardous Decomposition of Products	Will not decompose

11. TOXOLOGICAL INFORMATION	
Acute Toxicity	Non toxic
Skin & eye contact	No adverse effect
Chronic Toxicity	Based on available data, the classification criteria are not met.
Carcinogenicity	Based on available data, the classification criteria are not met.
Mutagenicity	Based on available data, the classification criteria are not met.
Reproductive Hazards	Based on available data, the classification criteria are not met.

12. ECOLOGICAL INFORMATION	
Toxicity	No ecological damage caused by this product.
Persistence and degradability	Not applicable
Bioaccumulative Potential Product	No bio-accumulating hazard.
Mobility in soil	No hazard
Results of PBT and vPvB assessment	Not classified as persistent, bioaccumulating and toxic (PBT).
Other adverse effects	No ecological damage caused by this product.
Effect on ozone layer	None
Effect on the global warming (CO2=1)	0

13. DISPOSAL CONSIDERATIONS	
Disposal Methods	 Do not discharge into any place where its accumulation could be dangerous.
Metrious	Vent to atmosphere in a well-ventilated place.
Disposal of Packaging	The container is the property of the supplier and the disposal of the containers must only be handled by the supplier.

14. TRANSPORT INFORMATION	
Road Transportation	
UN No.	1006 gas
	1755 liquid
Shipping Name	Argon



Please ensure that this SDS is received by the appropriate persons

Review Date: 18/07/2022 v01 Emergency: 0860 02 02 02 Document Number: AFX-SDS-0021

ERG No.	121
Class	2.1
Subsidiary Risk	Non- flammable, toxic gases
Hazchem Warning	Non-Toxic, non-flammable Gas
Sea Transportation	
IMDG	1006 gas
	1755 liquid
Shipping Name	Argon
ERG No.	121
Class	2.1
Subsidiary Risk	Non- flammable, toxic gases
Label	Non-Toxic non-flammable Gas
Air Transportation	
ICAO/IATA Code	1006 gas
	1755 liquid
Class	2.1
Packing Group:	-
Packaging	- Cargo: 150 kg
instructions	- Passenger: 75 kg

15. REGULATOR	Y INFORMATION
EEC Hazard class: non-Toxic, non-Corrosive gas. National legislation OHSact and Regulations 85 of 1993.	
SANS 11014:2010 Edition 1	Safety data sheet for chemical products - Content and order of sections
SANS 10228:2012 Edition 6	The identification and classification of dangerous goods for transport by road and rail modes
SANS 10234:2019 Edition 2	Globally Harmonized System of classification and labelling of chemicals (GHS)
SUPPLEMENT TO SANS 10234 Edition 1	List of classification and labelling of chemicals in accordance with the Globally Harmonized System (GHS)

16. OTHER INFORMATION

- Ensure all national/local regulations are observed.
- Ensure users and relevant persons understand the asphyxiation hazard
- Regularly check supplier's information sources for updated versions of SDS's

18/07/2022 v01

Bibliography

Compressed Gas Association, Arlington, Virginia Handbook of Compressed Gases - 3rd Edition Matheson Gas Data Book - 6th Edition

SANS 11014 - Safety data sheet for chemical products: Content and order of sections

SANS 10234 - List of classification and labelling of chemicals in accordance with the Globally Harmonized System (GHS)

SANS 10265 – Classification and Labelling of Dangerous Substances

EXCLUSION OF LIABILITY

Whilst AFROX made best endeavour to ensure that the information contained in this publication is accurate at the date of publication, AFROX does not accept liability for an

inaccuracy or liability arising from the use of this information, or the use, application, adaptation or process of any products described herein.