

#### Δir

# Please ensure that this SDS is received by the appropriate persons

1. PRODUCT	AND COMPANY IDENTIFICATION
Product	Air
Synonym	Air
Chemical	20.9% O <sub>2</sub> bal N <sub>2</sub>
Formula	
Trade Name	Air Dry
	Air Tec
	Air IG Zero
Colour Coding	Grey
Product Code	13-KB / 13-RC
	12-RC
	513207-IE-C/ 513207-SE-C
Company	African Oxygen Limited
Identification	Grayston Office Park Building 7
	128 Peter Road Sandown, Sandton,
	2196
	Tel. No: (011) 490-0400
	Fax No: (011) 490-0530
	Email:
	customer.service@afrox.linde.com
	www.afrox.com
Emorgoney	www.aiiux.coiii
Emergency Numbers	0860 02 02 02 (Afrox)

2. HAZARDII	DENTIFICATION
Classification	- Classification under South African     Hazardous Chemical Substances     Regulations subsequently amended.     (HCS)     - Classification under the Globally     Harmonized System of classification and     labelling of chemicals (GHS)
Emergency Overview	Colour: None Odour: None Taste: None Physical State: Gas Form: Gas under pressure
Adverse Health Effects	- None
Chemical Hazards	- None
Biological Hazards	- None
Vapour Inhalation	No adverse effects for this product
GHS Classification	- Gas under pressure
GHS Pictogram	
GHS Signal Words	Warning
GHS Hazard Statements	- H280: Contains gas under pressure, may explode if heated

GHS Precautionary Statements	Storage: - P403 : Store in a well-ventilated place. Prevention: - P280 : Wear protective gloves/eye protection/face protection. Response: - None Disposal - None
Other Hazards that do not result in classification	- Contains gas under pressure; may explode if heated.

3. COMPOSITION OF INGREDIENTS	
Chemical name	Air
Chemical family	Air
CAS No	Oxygen 7782-44-7
	Nitrogen 7727-37-9
UN No	UN 1002
ERG No	122
Hazard class	2.2
Hazchem Warning	Gas under pressure

4. FIRST All	D MEASURES
Eye contact	The liquid may cause frostbite - Rinse the eye with water immediately Remove contact lenses, if present and easy to do. Continue rinsing Flush thoroughly with water for at least 15 minutes Get immediate medical assistance. If
	medical assistance is not immediately available, flush an additional 15 minutes.
Skin Contact	The liquid may cause frostbite.  For exposure to liquid, immediately warm frostbite area with warm water not to exceed 41°C. Water temperature should be tolerable to normal skin.  Maintain skin warming for at least 15 minutes or until normal colouring and sensation have returned to the affected area.  In case of massive exposure, remove clothing while showering with warm water. Seek medical evaluation and treatment as soon as possible.
Ingestion	- Ingestion is not considered a potential route of exposure.
Inhalation	-Air will not cause irritation

5. FIRE-FIGHTING MEASURES	
Suitable	- Material will not burn. In case of fire in the
extinguishing	surroundings: use appropriate
media	extinguishing agent. May support combustion.
Unsuitable extinguishing media:	- None.



## Please ensure that this SDS is received by the appropriate persons

Review Date: 11/8/2022 ver1 Emergency: 0860 02 02 02 **Document Number: AFX-SDS-0024** 

Specific Hazards	- Contains gas under pressure; may explode if heated.
Special fire fighting procedures:	- In case of fire: Stop leak if safe to do so. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire.
Special protective equipment for firefighters:	- Exposed Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces a self-contained breathing apparatus.

6. ACCIDEN	TAL RELEASE MEASURES
Personal precautions, protective equipment and	- WARNING! Gas under pressure. Rapid release of gaseous Air through a pressure relief device (PRD) or valve can result is very cold and can cause frostbite.
emergency procedures:	<ul> <li>Evacuate area.</li> <li>Provide adequate ventilation.</li> <li>Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.</li> </ul>
	<ul> <li>In an enclosed or non-ventilated space, a self-contained breathing apparatus must be used.</li> </ul>
Environmental Precautions	- Prevent further leakage or spillage if safe to do so.
Methods and material for containment and cleaning up:	- Provide adequate ventilation.

	smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps were supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminants particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.
Conditions for safe storage, including any incompatibilit ies	-Containers should not be stored in conditions likely to encourage corrosion. Keep away from food, drink and animal feeding stuffs. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away

from sources of heat and ignition. Keep

pressure containers away from

combustible material.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION	
Occupational Exposure Hazards (HCS)	-Not specified
Engineering Control Measures	- Engineering control measures are preferred to reduce exposures. General methods include mechanical ventilation, process or personal enclosure, and control of process conditions. Administrative controls and personal protective equipment may also be required.  A Risk assessment should be conducted to evaluate the suitability of PPE to the task being performed
Personal Protection	- When allowed by a risk assessment Respiratory Protective Equipment (RPE) may be used. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected



#### Δir

# Please ensure that this SDS is received by the appropriate persons

Review Date: 11/8/2022 ver1 Emergency: 0860 02 02 02 Document Number: AFX-SDS-0024

	RPD. Self-contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres
Eyes	- Wear safety glasses
Hands	-Guideline: Protective gloves against mechanical risks.
	-Additional Information: Wear working gloves while handling containers
Body protection:	-Wear leather apron when handling liquid containers
Feet	- Wear safety shoes while handling containers

9. PHYSICAL AND CHEMICAL	. PROPERTIES
Chemical Name	<u>Air</u>
Chemical Symbol	O <sub>2</sub> and N <sub>2</sub>
Physical state	Gas
Form:	Gas
Colour:	Colourless
Odour:	Odourless
Odour Threshold:	No odour.
pH:	No effect in water
Melting Point:	-216.2°C
Boiling Point:	-194.3°C
Sublimation Point:	Not applicable
Critical Temp. (°C):	-146.95°C
Flash Point:	Not applicable
Evaporation Rate:	Not applicable.
Flammability ( gas):	Non-Flammable
Flammability limit - upper (%):	Not applicable
Flammability limit - lower(%):	Not applicable
Vapour pressure:	101.3 kPa@-194°C
Vapour density	1.20 @ 20°C
Relative density: Air=1	0.98 @ 20 °C
Solubility(ies)	
Solubility in Water:	0.018 l/kg water 20°C
Liquid density	0.874 kg/l @-194°C
Partition coefficient (n- octanol/water):	Not available
Autoignition Temperature:	Not applicable.
Decomposition Temperature:	Not known.
Kinematic viscosity:	No data available.
Dynamic viscosity:	Not applicable
Explosive properties:	Not applicable
Oxidising Properties:	Not applicable
Molecular weight	Oxygen 32.0 g/mol Nitrogen 28.014 g/mol

10. STABILITY AND REACTIVITY	
Reactivity	-Not reactive
Chemical stability	- Stable under normal conditions.

Possibility of hazardous reactions	- Gas under high pressure.
Conditions to avoid	- Overheating of cylinders. Never use cylinders as rollers or supports; or for any other purpose than the storage of Air
Incompatible Materials	None
Hazardous Decomposition of Products	Will not decompose

11. TOXOLOGICAL INFORMATION	
Acute Toxicity	Nontoxic
Skin & eye contact	No adverse effect
Chronic Toxicity	Based on available data, the
	classification criteria are not met.
Carcinogenicity	Based on available data, the
	classification criteria are not met.
Mutagenicity	Based on available data, the
	classification criteria are not met.
Reproductive Hazards	Based on available data, the
	classification criteria are not met.

12. ECOLOGICAL INFORMATION	
Toxicity	No ecological damage caused by this product.
Persistence and degradability	Not applicable
Bioaccumulative Potential Product	No bio-accumulating hazard.
Mobility in soil	No hazard
Results of PBT and vPvB assessment	Not classified as persistent, bio- accumulating and toxic (PBT).
Other adverse effects	No ecological damage caused by this product.
Effect on ozone layer	None
Effect on the global warming (CO2=1)	No effect on global warming

13. DISPOSA	L CONSIDERATIONS
Disposal Methods	<ul> <li>Do not discharge into any place where its accumulation could be dangerous. Vent to atmosphere in a well-ventilated place.</li> </ul>
Disposal of Packaging	The container is the property of the supplier and the disposal of the containers must only be handled by the supplier.

TRANSPORT INFORMATION		
14. TRANSPORT INFORMATION		
Road Transportation		
UN No.	UN 1002	
Shipping Name	Air	
ERG No.	122	
Class	2.2	
Subsidiary Risk	Non- flammable, non-toxic gases	
Hazchem Warning	Non-Toxic, non-flammable Gas	



#### Δir

### Please ensure that this SDS is received by the appropriate persons

Review Date: 11/8/2022 ver1 Emergency: 0860 02 02 02 Document Number: AFX-SDS-0024

Sea Transportation	
IMDG	1002
Shipping Name	Air
ERG No.	122
Class	2.2
Subsidiary Risk	Non- flammable, non-toxic gases
Label	Non-Toxic non-flammable Gas
Air Transportation	
ICAO/IATA Code	1002
Class	2.2
Packing Group:	NA
Packaging	- Cargo: 150 kg
instructions	- Passenger: 75 kg

15. REGULATOR	Y INFORMATION
EEC Hazard class: non-Toxic, non-Corrosive gas. National legislation OHSact and Regulations 85 of 1993.	
SANS 11014:2010 Edition 1	Safety data sheet for chemical products - Content and order of sections
SANS 10228:2012 Edition 6	The identification and classification of dangerous goods for transport by road and rail modes
SANS 10234:2019 Edition 2	Globally Harmonized System of classification and labelling of chemicals (GHS)
SUPPLEMENT TO SANS 10234 Edition 1	List of classification and labelling of chemicals in accordance with the Globally Harmonized System (GHS)

#### **16. OTHER INFORMATION**

- Ensure all national/local regulations are observed.
- Ensure users and relevant persons understand the asphyxiation hazard
- Regularly check supplier's information sources for updated versions of SDS's

Revision Date 4/8/2022 v01

### **Bibliography**

Compressed Gas Association, Arlington, Virginia Handbook of Compressed Gases - 3rd Edition Matheson Gas Data Book - 6th Edition

SANS 11014 - Safety data sheet for chemical products:

Content and order of sections

SANS 10234 - List of classification and labelling of chemicals in accordance with the Globally Harmonized System (GHS) SANS 10265 – Classification and Labelling of Dangerous Substances

#### **EXCLUSION OF LIABILITY**

Whilst AFROX made best endeavour to ensure that the information contained in this publication is accurate at the date of publication, AFROX does not accept liability for an inaccuracy or liability arising from the use of this information, or the use, application, adaptation or process of any products described herein.